AD NUMBER
AD464628
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; FEB 1965. Other requests shall be referred to Office of Naval Research, One Liberty Center, 875 North Randolph Street, Arlington, VA 22203-1995.
AUTHORITY
ONR ltr, 4 May 1977

UNCLASSIFIED

AD 464628

DDC

JUN 16 1965

TISIA B

HYDRONAUTICS, incorporated
research in hydrodynamics

Research, consulting, and advanced engineering in the fields of NAVAL
and INDUSTRIAL HYDRODYNAMICS. Offices and Laboratory in the
Washington, D. C., area: Pindell School Road, Howard County, Laurel, Md.

HYDRONAUTICS, Incorporated

TECHNICAL REPORT 231-6

SURFACE CURRENTS DUE TO A
SUBMERGED DISTURBANCE
IN A STRATIFIED OCEAN

By

K. K. Wong

February 1965

Prepared Under

Office of Naval Research
Department of the Navy
Contract No. Nonr 3688(00)
NR 220-016

HYDRONAUTICS, Incorporated

-1-

TABLE OF CONTENTS

HYDRONAUTICS, Incorporated

LIST OF FIGURES

HYDRONAUTICS, Incorporated

NOTATION

A	Source strength
b	Exponent of density stratification
f	Depth of submergence of disturbances
g	Acceleration due to gravity
H	Depth of thermocline
M	Quadrupole strength
N	Vaisala frequency
t	Time
u,v	Velocity components in x,y direction respectively
U,V	Transformed velocity components
x,y	Cartesian coordinates
α	Horizontal component of wave number
ω	Frequency
$\bar{\rho}$	Equilibrium density
τ	Thickness of thermocline
$\delta(x)$	Dirac delta function
φ	Fourier transform of V

HYDRONAUTICS, Incorporated

-1-

INTRODUCTION

A submerged disturbance in a stratified ocean will, in general, generate motions that are quite different from those generated in a homogeneous ocean. By stratification we mean a density stratification due to either the presence of a salinity or temperature gradient or both, the fluid being assumed to be incompressible. The difference is not simply a modification of the motion by the density stratification, which is slight in a real ocean, but rather the appearance of other forms of motion whose existence depends entirely on the density stratification. The difference, then, is one of kind and not simply one of degree.

In this report, the surface currents, i.e., currents at the air-sea interface due to a two-dimensional submerged disturbance, are considered. The equilibrium density profile of the ocean is assumed to be of the form shown in Figure 1a. This profile is chosen for its simplicity and also for its close approximation to reality. The disturbance is assumed to be always below the thermocline: It is a quadrupole of constant strength amplitude and with a simple harmonic time dependency. In spite of its simplicity it provides a time scale (inverse frequency) and length scale (proportional to its depth below the thermocline) characterizing the disturbance.

In the Appendix similar calculations are carried out for another class of density profiles shown schematically in Figure 1b.

HYDRONAUTICS, Incorporated

FORMULATION OF THE PROBLEM

The equilibrium density profile of the ocean is taken to be of the following form:

$$\overline{\rho} = \begin{cases} \rho_1 & \text{in } R_0: \ (f + H > y > f + \tau) \\ \rho_2\, e^{-2b_1(y-f)} & \text{in } R_1: \ (f + \tau > y > f) \\ \rho\, e^{-2b_2 y} & \text{in } R_2: \ (f > y > -\infty) \end{cases}$$

The fluid is assumed to be inviscid and incompressible. In the above, ρ, ρ_1, ρ_2, f, τ and H are all positive real constants. A schematic diagram of the profile is shown in Figure 1a.

We are interested in the currents at the free surface $y = f + H$ generated by a two-dimensional quadrupole of constant strength amplitude M and with a simple harmonic time dependency of frequency ω located at the origin of the coordinate system $(x = 0, y = 0)$. The solution for a periodic source of strength A is found first. From this solution, the one for a quadrupole is obtained by differentiation.

It is convenient to work with the transformed velocity components U and V defined by

$$U = \overline{\rho}^{\frac{1}{2}} u$$

$$V = \overline{\rho}^{\frac{1}{2}} v$$

where

u, v are the physical velocity components.

Since the forcing function is simple harmonic, so, after a sufficient time has elapsed for the transients to die away, the whole system would acquire a simple harmonic motion of the same frequency. In this final quasi-steady state, the time dependency of the dependent variables may be factored out so that

$$U(x,y,t) = \overline{U}(x,y)e^{-i\omega t}$$

$$V(x,y,t) = \overline{V}(x,y)e^{-i\omega t}$$

If the disturbance is weak, so that the resulting motion may be considered as small perturbations about the state of hydrostatic equilibrium, then the differential equations governing $\overline{V}$ in the different regions are (see Wong, 1965)

in R_o $\qquad \dfrac{\partial^2 \overline{V}_o}{\partial y^2} + \dfrac{\partial^2 \overline{V}_o}{\partial x^2} = 0$ [1]

in R_1 $\qquad \dfrac{\partial^2 \overline{V}_1}{\partial y^2} + \left(1 - \dfrac{2gb_1}{\omega^2}\right) \dfrac{\partial^2 \overline{V}_1}{\partial x^2} - b_1{}^2 \overline{V}_1 = 0$ [2]

in R_2 $\qquad \dfrac{\partial^2 \overline{V}_2}{\partial y^2} + \left(1 - \dfrac{2gb_2}{\omega^2}\right) \dfrac{\partial^2 \overline{V}_2}{\partial x^2} - b_2{}^2 \overline{V}_2$

$$= 2\pi \sqrt{\rho}\, A\, \delta(x)\, [\dot{\delta}(y) - b_2 \delta(y)] \qquad [3]$$

where δ denotes the Dirac delta function and a dot denotes a differentiation. Subscripts have been added to $\overline{V}$ to denote the function in the various regions. The right hand side of Equation [3] represents the source.

The surface current is essentially due to the formation and propagation of internal waves. Because of the much larger density discontinuity at the air-sea interface the vertical movements there are negligible for all practical purposes. Therefore, the boundary condition there can be taken to be

$$\overline{V}_o = 0 \quad \text{at } y = f + H \tag{4}$$

At $y = f$ and $y = f + \tau$ both $\overline{U}$ and $\overline{V}$ have to be continuous. This gives rise to the following boundary conditions:

$$\overline{V}_o = \overline{V}_1 \quad \text{at } y = f + \tau \tag{5}$$

$$\overline{V}_1 = \overline{V}_2 \quad \text{at } y = f \tag{6}$$

$$\frac{\partial \overline{V}_o}{\partial y} = b_1 \overline{V}_1 + \frac{\partial \overline{V}_1}{\partial y} \quad \text{at } y = f + \tau \tag{7}$$

$$b_1 \overline{V}_1 + \frac{\partial \overline{V}_1}{\partial y} = b_2 \overline{V}_2 + \frac{\partial \overline{V}_2}{\partial y} \quad \text{at } y = f \tag{8}$$

HYDRONAUTICS, Incorporated

The last two equations were obtained from the equation of continuity, viz.,

$$\frac{\partial \overline{U}}{\partial x} + \frac{\partial \overline{V}}{\partial y} + b \; \overline{V} = 2\pi \sqrt{\rho} \; A \; \delta(x) \; \delta(y)$$

which becomes

$$\frac{\partial \overline{U}_0}{\partial x} + \frac{\partial \overline{V}_0}{\partial y} = 0 \qquad \text{in } R_0 \qquad\qquad [9]$$

$$\frac{\partial \overline{U}_1}{\partial x} + \frac{\partial \overline{V}_1}{\partial y} + b_1 \overline{V}_1 = 0 \qquad \text{in } R_1 \qquad\qquad [10]$$

$$\frac{\partial \overline{U}_2}{\partial x} + \frac{\partial \overline{V}_2}{\partial y} + b_2 \overline{V}_2 = 2\pi \sqrt{\rho} \; A \; \delta(x) \; \delta(y) \qquad \text{in } R_2 \qquad [11]$$

In addition to the above conditions other conditions have to be imposed at infinity to insure a unique solution. These additional conditions will be discussed as they arise.

SURFACE CURRENTS DUE TO A SUBMERGED SOURCE

Let φ_i denote the Fourier transform of $\overline{V}_i$ with respect to x so that

$$\varphi_i = \int_{-\alpha}^{+\infty} \overline{V}_i \; e^{-i\alpha x} dx \qquad , \qquad i = 0, 1, 2.$$

Then, from the equations governing $\overline{V}_1$ the following set of equations for φ_1 is obtained:

$$\ddot{\varphi}_0 - \alpha^2 \varphi_0 = 0 \qquad \text{for } f + H > y > f + \tau \qquad [12]$$

$$\ddot{\varphi}_1 - \left[b_1{}^2 + \left(1 - \frac{2gb_1}{\omega^2}\right)\alpha^2\right] \varphi_1 = 0 \qquad \text{for } f + \tau > y > f \qquad [13]$$

$$\ddot{\varphi}_2 - \left[b_2{}^2 + \left(1 - \frac{2gb_2}{\omega^2}\right)\alpha^2\right] \varphi_2 = 2\pi\, A \sqrt{\rho}\left[\mathring{\delta}(y) - b\delta(y)\right] \text{ for } y < f \qquad [14]$$

$$\varphi_0 = 0 \qquad \text{at } y = f + H \qquad [15]$$

$$\varphi_0 = \varphi_1 \qquad \text{at } y = f + \tau \qquad [16]$$

$$\varphi_1 = \varphi_2 \qquad \text{at } y = f \qquad [17]$$

$$\dot{\varphi}_0 = b_1 \varphi_1 + \dot{\varphi}_1 \qquad \text{at } y = f + \tau \qquad [18]$$

$$b_1 \varphi_1 + \dot{\varphi}_1 = b_2 \varphi_2 + \ddot{\varphi}_2 \text{ at } y = f \qquad [19]$$

The most general solutions of Equations [12] to [14] are respectively,

$$\varphi_0 = A_0 e^{-|\alpha|y} + B_0 e^{+|\alpha|y} \qquad [20]$$

$$\varphi_1 = A_1 e^{-\beta_1 y} + B_1 e^{+\beta_1 y} \qquad [21]$$

$$\varphi_2 = A_2 e^{-\beta_2 y} + B_2 e^{+\beta_2 y} + H(y)\,\pi\,A\,\sqrt{\rho}\left(\frac{b_2}{\beta_2} + 1\right) e^{-\beta_2 y}$$

$$+ [1 - H(y)]\pi\,A\,\sqrt{\rho}\left(\frac{b_2}{\beta_2} - 1\right) e^{+\beta_2 y} \qquad [22]$$

where A_i, B_i, are arbitrary functions of the parameter α, $H(y)$ denotes the Heaviside function and β_1, β_2 are given by

$$\beta_1 = +\sqrt{b_1^2 + \left(1 - \frac{2gb_1}{\omega^2}\right)\alpha^2}$$

$$\beta_2 = +\sqrt{b_2^2 + \left(1 - \frac{2gb_2}{\omega^2}\right)\alpha^2}$$

Because of Equation [15], φ_0 must be of the form

$$\varphi_0 = A_0 \sinh |\alpha|\, [(f + H) - y] \qquad [23]$$

A_0 now is some other arbitrary function of α. Because of conditions at $y \to -\infty$, $A_2 \equiv 0$ and Equation [22] becomes

$$\varphi_2 = B_2 e^{+\beta_2 y} + H(y) \ \pi \ A \ \sqrt{\rho} \left(\frac{b_2}{\beta_2} + 1 \right) e^{-\beta_2 y}$$

$$+ \ [1 - H(y) \ ] \ \pi \ A \ \sqrt{\rho} \left(\frac{b_2}{\beta_2} - 1 \right) e^{+\beta_2 y} \qquad [24]$$

Substituting known expressions for φ_1 into Equations [16] to [19] yield the following set of four equations for the determination of A_0, A_1, B_1 and B_2 :

$$A_0 \ \sinh |\alpha| \ (H - \tau) = A_1 e^{-\beta_1 (f+\tau)} + B_1 e^{+\beta_1 (f+\tau)}$$

$$-|\alpha| A_0 \ \cosh |\alpha| \ (H - \tau) = A_1 (b_1 - \beta_1)e^{-\beta_1 (f+\tau)} + B_1 (b_1 + \beta_1)e^{\beta_1 (f+\tau)}$$

$$B_2 e^{\beta_2 f} + \pi \ A \ \sqrt{\rho} \left(\frac{b_2}{\beta_2} + 1 \right) e^{-\beta_2 f} = A_1 e^{-\beta_1 f} + B_1 e^{+\beta_1 f}$$

$$B_2 (b_2 + \beta_2)e^{\beta_2 f} + (b_2 - \beta_2) \ \pi \ A \ \sqrt{\rho} \left(\frac{b_2}{\beta_2} + 1 \right) e^{-\beta_2 f} = A_1 (b_1 - \beta_1)e^{-\beta_1 f}$$

$$+ \ B_1 (b_1 + \beta_1)e^{+\beta_1 f}$$

Solving the above equations simultaneously, A_0 is found to be:

$$A_0 = - \frac{4\pi A \ \sqrt{\rho} \ (b_2 + \beta_2)e^{-\beta_2 f}}{(\xi + \eta)(b_1 - b_2 - \beta_1 - \beta_2)e^{+\beta_1 \tau} + (\xi - \eta)(b_1 - b_2 + \beta_1 - \beta_2)e^{-\beta_1 \tau}}$$

$$[25]$$

where

$$\xi = \sinh |\alpha| \ (H - \tau)$$

$$\eta = \frac{1}{\beta_1} \left[\ |\alpha| \ \cosh |\alpha| \ (H - \tau) + b_1 \ \sinh |\alpha| \ (H - \tau) \right]$$

Taking the inverse transform, V_0 is expressed as a Fourier integral

$$\bar{V}_0 = \frac{1}{2\pi} \int_{-\infty}^{+\infty} A_0 \ \sinh |\alpha| \ [(f + H) - y] e^{i\alpha x} \ d\alpha \qquad [26]$$

$\bar{U}_0$ can be found from Equation [9] as follows:

$$\frac{\partial \bar{U}_0}{\partial x} = - \frac{\partial \bar{V}_0}{\partial y}$$

$$= + \frac{1}{2\pi} \int_{-\infty}^{+\infty} A_0 |\alpha| \ \cosh |\alpha| \ [(f + H) - y] e^{i\alpha x} \ d\alpha$$

$$\bar{U}_0 = \frac{1}{2\pi i} \int_{-\infty}^{+\infty} A_0 \ \frac{|\alpha|}{\alpha} \ \cosh |\alpha| \ [(f + H) - y] e^{i\alpha x} \ d\alpha \quad [27]$$

In arriving at the last expression for $\bar{U}_0$ the fact that $\bar{U}_0$ is antisymmetric in x was used.

The surface current induced by the source is, then, given by

$$\tilde{u}_o = \frac{e^{-i\omega t}}{2\pi i \sqrt{\rho_1}} \int_{-\infty}^{+\infty} A_o \frac{|\alpha|}{\alpha} e^{i\alpha x} d\alpha \qquad [28]$$

In what follows we shall always assume that

$$\epsilon = \frac{\rho_2 - \rho_1}{\rho_2} << 1$$

First consider the simplest special case where the thermocline is a discontinuity ($\tau = 0$) and the layer below the thermocline is homogeneous ($b_2 = 0$, $\rho = \rho_2$). For this special case

$$A_o = \frac{2\pi A \sqrt{\rho_2} \, \alpha \, e^{-|\alpha|f}}{|\alpha| e^{+|\alpha| H} - \frac{g\epsilon\alpha^2}{\omega^2} \sinh|\alpha|H}$$

Therefore

$$\tilde{u}_o = -i A e^{-i\omega t} \int_{-\infty}^{+\infty} \frac{\frac{\omega^2 |\alpha|}{\alpha} e^{-|\alpha|(f+H)} e^{i\alpha x}}{\omega^2 - g\epsilon |\alpha| e^{-|\alpha|H} \sinh|\alpha|H} d\alpha \qquad [29]$$

Since the integrand has poles on the real axis, the integral is
undefined. Under such circumstances it is usual to deform the
path of integration so that it goes around instead of through
the poles. How the path is to be deformed depends on additional
physical information. Here, the surface current is a conse-
quence of the formation and propagation of interfacial waves at
the thermocline. These waves are all outgoing waves from the
central region of disturbances. Therefore, the current also
possesses this outgoing wave property. For such a situation the
path has to be deformed slightly above the real axis when $x < 0$
and slightly below when $x > 0$. The path of integration can be
closed by a large semicircle in the upper half plane when $x > 0$
and the lower half plane when $x < 0$. It can easily be shown
that the contribution from the integration along the semicircle
vanishes as the radius tends to infinity. Since the integrand
is analytic except for poles, the integral may be evaluated by
the method of residues. The contributions from the poles having
a non-vanishing imaginary part will vanish exponentially with
x because of the factor $e^{i\alpha x}$. Therefore, for x large and posi-
tive only the positive real roots of the equation

$$\omega^2 - g\epsilon\alpha\, e^{-\alpha H} \sinh \alpha H = 0 \qquad\qquad [30]$$

are important. This equation is plotted in Figure 2. It is
seen that for a given ω there is only one real positive α,
say, α_0 which satisfies the above equation.

HYDRONAUTICS, Incorporated

Hence, for large and positive x

$$\tilde{u}_0 \sim - \pi A \frac{\omega \, e^{-\alpha_0(f+H)}}{\left(\dfrac{d\sigma}{d\alpha}\right)_{\alpha_0}} e^{i(\alpha_0 x - \omega t)} \qquad [31]$$

where

$$\sigma^2 = g\epsilon \, |\alpha| e^{-|\alpha|H} \sinh|\alpha|H$$

and α_0 is the positive real solution of Equation [30].

Next consider the effects of a thin thermocline on the surface currents generated by the source, i.e., τ is small compared with H but finite. As in the previous case b_2 is set equal to zero. Now

$$b_1 = \frac{1}{2\tau} \ln (1 + \epsilon) \approx \frac{\epsilon}{2\tau}$$

therefore

$$\beta_1 \tau = \tau \sqrt{b_1^2 + \left(1 - \frac{2gb_1}{\omega^2}\right) \alpha^2}$$

$$= \sqrt{\frac{\epsilon^2}{4} + \alpha^2 \tau^2 - g \epsilon \tau \frac{\alpha^2}{\omega^2}}$$

If τ is small, its effects on the dispersion relation (Equation [30]) may be expected to be small. The third term under the square root can then be approximated by

$$\frac{\tau \, \alpha}{e^{-\alpha H} \sinh \alpha H} = \frac{2\tau\alpha}{1 - e^{-2\alpha H}}$$

$$= \begin{cases} 2\tau\alpha & \text{for } \alpha H \text{ large} \\ \\ \dfrac{\tau}{H} & \text{for } \alpha H \text{ small} \end{cases}$$

From Equation [31] it is seen that only waves with small wave numbers produce significant currents because of the factor $e^{-|\alpha|(f+H)}$. Therefore, $\alpha\tau$ is small since τ/H is assumed to be small. Hence, $\beta_1\tau$ is small and we have

$$e^{\beta_1\tau} \approx 1 + \beta_1\tau$$

$$e^{-\beta_1\tau} \approx 1 - \beta_1\tau$$

Under these circumstances and with $b_2 = 0$, A_0 simplifies to

$$A_0 = \frac{2\pi \, A \, \sqrt{\rho_2} \, |\alpha| e^{-|\alpha|f}}{|\alpha|(1 + |\alpha|\tau)e^{-|\alpha|H} - g\epsilon \dfrac{\alpha^2}{\omega^2} \sinh|\alpha|H}$$

and the surface current to

$$\tilde{u}_o = -i\,A\,e^{-i\omega t} \int_{-\infty}^{+\infty} \frac{\dfrac{\omega^2\,|\alpha|}{\alpha(1+|\alpha|\tau)}\,e^{-|\alpha|(f+H-\tau)}\,e^{i\alpha x}\,d\alpha}{\left[\omega^2 - \dfrac{g\epsilon\,|\alpha|}{1+|\alpha|\tau}\,e^{-|\alpha|(H-\tau)}\,\sinh|\alpha|(H-\tau)\right]} \qquad [32]$$

The integral in Equation [32] can be evaluated as in the previous case where the thermocline is a discontinuity. For large positive x the surface current is given by

$$\tilde{u}_o \sim -\pi A\,\frac{\omega\,e^{-\alpha_o(f+H-\tau)}\,e^{i(\alpha_o x-\omega t)}}{\left(1+\alpha_o\tau\right)\left(\dfrac{d\gamma}{d\alpha}\right)_{\alpha_o}} \qquad [33]$$

where $\gamma^2 = \dfrac{g\epsilon\,|\alpha|}{1+|\alpha|\tau}\,e^{-|\alpha|(H-\tau)}\,\sinh|\alpha|(H-\tau)$

and α_o is the positive real root of the following equation:

$$\omega^2 - \frac{g\epsilon\alpha}{1+\alpha\tau}\,e^{-\alpha(H-\tau)}\,\sinh\alpha(H-\tau) = 0 \qquad [34]$$

Finally, let us consider the effects of a stratification below the thermocline; the thermocline is here taken to be a discontinuity, i.e., $\tau = 0$, b_2 is small so that

$$\beta_2 = \sqrt{b_2^2 + \left(1 - \frac{2gb_2}{\omega^2}\right)\alpha^2} \approx |\alpha| \sqrt{1 - \frac{2gb_2}{\omega^2}}$$

Under such circumstances A_o simplifies to

$$A_o \approx \frac{2\pi A\sqrt{\rho} \sqrt{1 - \frac{2gb_2}{\omega^2}} e^{-\sqrt{1 - \frac{2gb_2}{\omega^2}}|\alpha| f}}{\sqrt{1 - \frac{2gb_2}{\omega^2}} \sinh |\alpha| H + \cosh |\alpha| H - \frac{g\epsilon|\alpha|}{\omega^2} \sinh |\alpha| H}$$

and the surface current to

$$\tilde{u}_o \approx -1 A e^{-i\omega t} \sqrt{1 - \frac{2gb}{\omega^2}} \int_{-\infty}^{+\infty} \frac{\frac{|\alpha|}{\alpha} e^{-\sqrt{1 - \frac{2gb_2}{\omega^2}}|\alpha| f} e^{i\alpha x} d\alpha}{\sqrt{1 - \frac{2gb_2}{\omega^2}} \sinh|\alpha|H + \cosh|\alpha|H - \frac{g\epsilon|\alpha|}{\omega^2} \sinh|\alpha|H}$$

[35]

When $\omega^2 < 2gb_2$, the integrand has no pole on the real axis. This can be shown as follows: Let α_o be a real root of the equation

$$\sqrt{1 - \frac{2gb_2}{\omega^2}} \sinh |\alpha| H + \cosh |\alpha| H - \frac{g\epsilon|\alpha|}{\omega^2} \sinh |\alpha| H = 0$$

[36]

HYDRONAUTICS, Incorporated

If $\omega^2 < 2gb_2$ then α_0 has to satisfy the following pair of equations:

$$\sqrt{\frac{2gb_2}{\omega^2} - 1} \; \sinh |\alpha_0| \; H = 0$$

$$\cosh |\alpha_0| \; H - \frac{g\epsilon |\alpha|}{\omega^2} \sinh |\alpha_0| \; H = 0$$

but this is impossible. Therefore, Equation [36] has no real solution for $\omega^2 < 2gb_2$. However, for every $\omega^2 > 2gb_2$ there is a unique positive solution (see Figure 2). Let this be denoted by α_0. Then for large positive x the surface current is given by

$$\tilde{u}_0 \sim 2\pi A \; \frac{\sqrt{1 - \frac{2gb_2}{\omega^2}} \; e^{-\sqrt{1 - \frac{2gb_2}{\omega^2}} \, \alpha_0 f} \; e^{i(\alpha_0 x - \omega t)}}{\left(\frac{d\zeta}{d\alpha}\right)_{\alpha_0}} \qquad [37]$$

where

$$\zeta = \sqrt{1 - \frac{2gb_2}{\omega^2}} \; \sinh |\alpha| \; H + \cosh |\alpha| \; H - \frac{g\epsilon |\alpha|}{\omega^2} \sinh |\alpha| \; H$$

SURFACE CURRENTS DUE TO A SUBMERGED QUADRUPOLE

The quadrupole under consideration has a configuration shown in Figure 3. The strength M of the quadrupole is given by

$$M = A^2 \Delta^3$$

HYDRONAUTICS, Incorporated

where A is the strength of the individual sources and sinks and
Δ is the distance separating them.

The surface current w due to a quadrupole of strength
amplitude M and time dependence $e^{-i\omega t}$ located at the origin is
obtained by differentiating the source solution, i.e., $\tilde{u}_o$ with
respect to x and replacing A by M.

Let us choose H as the reference length and $\sqrt{H/g\epsilon}$ as the ref-
erence time and introduce the following dimensionless variables

$$t' = t/\sqrt{H/g\epsilon}$$

$$x' = x/H$$

$$f' = f/H$$

$$\tau' = \tau/H$$

$$\alpha_o' = \alpha_o H$$

$$\omega' = \omega\sqrt{\frac{H}{g\epsilon}}$$

The surface currents generated by the quadrupole corre-
sponding to the three cases analyzed in the previous section
for the source are found to be

Case I $\tau' = 0$, $b_2 = 0$

For large positive x the surface current due to the quadrupole is given by

$$w \sim \left(\frac{\pi M}{H^3}\right) \frac{\omega'(\alpha_0')^2 \; e^{-\alpha_0'(f'+1)} \; e^{i(\alpha_0'x'-\omega't')}}{\left|\dfrac{d\sigma'}{d\alpha'}\right|_{\alpha_0'}}$$

The magnitude of the current is

$$|w| \sim \left(\frac{\pi M}{H^3}\right) \frac{\omega'(\alpha_0')^2 \; e^{-\alpha_0'(f'+1)}}{\left|\dfrac{d\sigma'}{d\alpha'}\right|_{\alpha_0'}}$$

$$= \left(\frac{\pi M}{H^3}\right) U^* \qquad\qquad\qquad [38]$$

where

$$(\sigma')^2 = |\alpha'| \; e^{-|\alpha'|} \; \sinh|\alpha'|$$

and α_0', which is the asymptotic wave number of the current, is the positive real root of the equation

$$(\omega')^2 - \alpha' \; e^{-\alpha'} \; \sinh \alpha' = 0$$

HYDRONAUTICS, Incorporated

-19-

Case I1 $\tau' \neq 0$, $b_2 = 0$

For large positive x the surface current due to the quadrupole is

$$w \sim \left(\frac{\pi M}{H^3}\right) \frac{\omega'(\alpha_0')^2 \, e^{-\alpha_0'(f'+1-\tau')} \, e^{i(\alpha_0'x'-\omega't')}}{(1 + \alpha_0'\tau') \left(\frac{d\gamma'}{d\alpha'}\right)_{\alpha_0'}}$$

The magnitude of the current is

$$|w| \sim \left(\frac{\pi M}{H^3}\right) \frac{\omega'(\alpha_0')^2 \, e^{-\alpha_0'(f'+1-\tau')}}{(1 + \alpha_0'\tau') \left(\frac{d\gamma'}{d\alpha'}\right)_{\alpha_0'}}$$

$$= \left(\frac{\pi M}{H^3}\right) U^* \hspace{3cm} [39]$$

where

$$(\gamma')^2 = \frac{|\alpha'|}{(1 + |\alpha'|\tau')} \, e^{-|\alpha'|(1-\tau')} \quad \sinh |\alpha'|(1 - \tau')$$

and α_0' is the positive root of

$$\omega'^2 - \frac{\alpha'}{1 + \alpha'\tau'} \, e^{-\alpha'(1-\tau')} \quad \sinh \alpha'(1 - \tau') = 0$$

When $\tau' = 0$, this case reduces to Case I.

HYDRONAUTICS, Incorporated

Case III $\tau' = 0$, $b_2 \neq 0$

For large positive x the surface current due to the quadrupole is

$$w \sim \left(\frac{\pi M}{H^3}\right) \frac{2\sqrt{1-\left(\frac{N'}{\omega'}\right)^2}\, e^{-\sqrt{1-\left(\frac{N'}{\omega'}\right)^2}\,\alpha_o'f'}\, e^{i(\alpha_o'x'-\omega't')}}{\left(\frac{d\zeta'}{d\alpha}\right)_{\alpha_o}}$$

$$|w| \sim \left(\frac{\pi M}{H^3}\right) \frac{2\sqrt{1-\left(\frac{N'}{\omega'}\right)^2}\, e^{-\sqrt{1-\left(\frac{N'}{\omega'}\right)^2}\,\alpha_o'f'}}{\left(\frac{d\zeta'}{d\alpha'}\right)_{\alpha_o'}}$$

$$= \left(\frac{\pi M}{H^3}\right) U^* \qquad\qquad [40]$$

where

$$\zeta' = \sqrt{1-\left(\frac{N'}{\omega'}\right)^2}\, \sinh|\alpha'| + \cosh|\alpha'| - \frac{\alpha'}{(\omega')^2}\sinh|\alpha'|$$

and α_o' is the positive real root of the equation

$$\zeta' = 0$$

as N' tends to zero this case tends to Case I.

DISCUSSION OF RESULTS

The surface current due to a two-dimensional quadrupole of constant strength amplitude and simple harmonic time dependency was determined analytically. It was found that the current is a consequence of the formation and propagation of interfacial waves at the thermocline. For large distances from the source of disturbances, the interfacial waves form a regular train of outgoing waves having a definite amplitude and wave number. The surface current also possesses these characteristics.

The asymptotic wave number of the surface current is the wave number of free waves at the thermocline. It depends solely on the density profile and the frequency of the disturbance but not at all on its nature or depth of submergence. In Figure 2 the asymptotic wave number, denoted by α_o, is plotted against the frequency ω for various density profiles. For a given frequency ω and the same H, a thicker thermocline retards the phase velocity, hence increases the wave number. A stratified layer below the thermocline, however, increases the phase velocity, hence reduces the wave number. When the stratification in the lower layer is so large that its Vaisala frequency $N = \sqrt{2gb_2}$ is greater than the frequency of the disturbance, interfacial waves at the thermocline will attenuate as they propagate because of energy transfer in the form of true internal waves to the lower layer.

HYDRONAUTICS, Incorporated

The asymptotic amplitude of the surface current depends on how effective the submerged disturbance is transmitting energy to that component of the interfacial wave which has a wave number equal to α_o (the wave number of free interfacial waves corresponding to the frequency ω of the submerged disturbance). In Figures 4 and 5 are shown the asymptotic amplitude of the surface current as a function of ω for various density profiles.

REFERENCE

1. Wong, K. K., "On Internal Gravity Waves Generated by Local Disturbances," HYDRONAUTICS, Incorporated Technical Report 231-5, February 1965.

HYDRONAUTICS, Incorporated

-23-

APPENDIX

First consider the surface currents due to an oscillating source of amplitude A and simple harmonic time dependence $e^{-i\omega t}$ located at $(x = 0, y = 0)$ in an ocean with the density profile shown in Figure 1b.

Express the physical vertical velocity component $v(x,y,t)$ as

$$v = \overline{\rho}^{\frac{1}{2}}V = \rho^{\frac{1}{2}}\,\overline{V}\,e^{-i\omega t} \qquad [A-1]$$

The differential equations and boundary conditions governing φ, the Fourier transform of $\overline{V}$ with respect to x, are:

$$\frac{d^2\varphi_1}{dy^2} - \left[b_1{}^2 + \left(1 - \frac{2gb_1}{\omega^2}\right)\alpha^2\right]\varphi_1 = 0, \qquad f < y < H \qquad [A-2]$$

$$\frac{d^2\varphi_2}{dy^2} - \left[b_2{}^2 + \left(1 - \frac{2gb_2}{\omega^2}\right)\alpha^2\right]\varphi_2 = 2\pi A\rho^{\frac{1}{2}}\left[\dot{\delta}(y) - b_2\,\delta(y)\right]$$

$$\text{for } -\infty < y < f \qquad [A-3]$$

$$\varphi_1 = 0 \qquad \text{at } y = f + H \qquad [A-4]$$

$$\varphi_1 = \varphi_2 \qquad \text{at } y = f \qquad [A-5]$$

$$b_1 \varphi_1 + \frac{d\varphi_1}{dy} = b_2 \varphi_2 + \frac{d\varphi_2}{dy} \qquad \text{at } y = f \qquad [A-6]$$

$$\varphi_2 \rightarrow C \qquad \text{as } y \rightarrow -\infty \qquad [A-7]$$

Solving these equations simultaneously it is found that

$$\varphi_1 = C \sinh \beta_1 [(f + H) - y] \qquad [A-8]$$

where

$$C = - \frac{2\pi A \rho^{\frac{1}{2}} (b_2 + \beta_2) e^{-\beta_2 f}}{(b_1 - b_2 - \beta_2) \sinh \beta_1 H - \beta_1 \cosh \beta_1 H} \qquad [A-9]$$

$$\beta_1 = \sqrt{b_1^2 + \left(1 - \frac{2gb_1}{\omega^2}\right)\alpha^2} \qquad [A-10]$$

$$\beta_2 = \sqrt{b_2^2 + \left(1 - \frac{2gb_2}{\omega^2}\right)\alpha^2} \qquad [A-11]$$

Therefore

$$V_1 = \frac{1}{2\pi} \int_{-\infty}^{+\infty} C \sinh \beta_1 [(f + H) - y] e^{i\alpha x} d\alpha \qquad [A-12]$$

HYDRONAUTICS, Incorporated

-25-

from which the surface current u_0 due to the oscillating source is found to be

$$u_0 = \left[\bar{\rho}(y = f + H) \right]^{\frac{1}{2}} \frac{e^{-i\omega t}}{2\pi} \int_{-\infty}^{+\infty} C\beta_1 \frac{e^{i\alpha x}}{i\alpha} \, d\alpha \qquad [A\text{-}13]$$

The surface current due to an oscillating quadrupole of amplitude M can easily be found from that due to the source. It is

$$\tilde{u}_0 = + \frac{e^{-i\omega t}}{i} M \int_{-\infty}^{+\infty} \frac{(b_2 + \beta_2) e^{-\beta_2 f} \beta_1 \alpha \, e^{i\alpha x} \, d\alpha}{(b_1 - b_2 - \beta_2) \sinh \beta_1 H - \beta_1 \cosh \beta_1 H} \qquad [A\text{-}14]$$

It has been assumed that

$$\epsilon = \frac{\rho - \bar{\rho}(y = f + H)}{\rho} << 1 \qquad [A\text{-}15]$$

Let it be further assumed that

$$\alpha >> b_1 \text{ or } b_2 \qquad [A\text{-}16]$$

so that

$$\beta_1 \approx |\alpha| \sqrt{1 - \frac{2gb_1}{\omega^2}}$$

$$\beta_2 \approx |\alpha| \sqrt{1 - \frac{2gb_2}{\omega^2}}$$

and expression [A-14] simplifies to

$$\tilde{u}_o \approx - e^{-i\omega t} \frac{M}{i} \sqrt{1 - \frac{2gb_2}{\omega^2}} \sqrt{1 - \frac{2gb_1}{\omega^2}} \times$$

$$\int_{-\infty}^{+\infty} \frac{|\alpha|\alpha\, e^{-\sqrt{1 - \frac{2gb_2}{\omega^2}}|\alpha|f}\, e^{i\alpha x}\, d\alpha}{\sqrt{1 - \frac{2gb_2}{\omega^2}} \sinh\sqrt{1 - \frac{2gb_1}{\omega^2}}|\alpha|H + \sqrt{1 - \frac{2gb_1}{\omega^2}} \cosh\sqrt{1 - \frac{2gb_1}{\omega^2}}|\alpha|H}$$

[A-17]

For large x, contributions to the integral in Equation [A-17] come from the real poles of the integrand only. Therefore, let us examine the roots of the equation

$$\sqrt{1 - \frac{2gb_2}{\omega^2}} \sinh\sqrt{1 - \frac{2gb_1}{\omega^2}}|\alpha|H + \sqrt{1 - \frac{2gb_2}{\omega^2}} \cosh\sqrt{1 - \frac{2gb_1}{\omega^2}}|\alpha|H = 0$$

[A-18]

HYDRONAUTICS, Incorporated

Assume $2gb_1 > 2gb_2$.

Case I: $w^2 < 2gb_2 < 2gb_1$

Equation [A-18] becomes

$$i \tan \sqrt{\frac{2gb_1}{w^2} - 1} \, |\alpha| H = -\sqrt{\frac{\sqrt{\frac{2gb_1}{w^2} - 1}}{\frac{2gb_2}{w^2} - 1}}$$

which has no real roots. Therefore

$$\tilde{u}_o = 0 \quad \text{for } w^2 < 2gb_2 < 2gb_1$$

Case II: $w^2 > 2gb_1 > 2gb_2$

Equation [A-18] becomes

$$\tanh \sqrt{1 - \frac{2gb_1}{w^2}} \, |\alpha| H = -\sqrt{\frac{1 - \frac{2gb_1}{w^2}}{1 - \frac{2gb_2}{w^2}}}$$

which also has no real roots. Therefore

$$\tilde{u}_o = 0 \quad \text{for } w^2 > 2gb_1 > 2gb_2$$

HYDRONAUTICS, Incorporated

-28-

Case III: $2gb_2 < \omega^2 < 2gb_1$

Equation [A-18] becomes

$$\tan \sqrt{\frac{2gb_1}{\omega^2} - 1} \; |\alpha| H = -\sqrt{\frac{\frac{2gb_1}{\omega^2} - 1}{1 - \frac{2gb_2}{\omega^2}}}$$

which has an infinite number of roots

$$\alpha_n = \pm \frac{n\pi - \tan^{-1}\sqrt{\frac{\frac{2gb_1}{\omega^2} - 1}{1 - \frac{2gb_2}{\omega^2}}}}{H\sqrt{\frac{2gb_1}{\omega^2} - 1}} \qquad n = 1,2 \ldots$$

For x > 0 and large

$$\tilde{u}_o = -\frac{2\pi M}{H}\sqrt{1 - \frac{2gb_2}{\omega^2}} \; x$$

$$\sum_{n=1}^{\infty} \frac{\alpha_n^2 \, e^{-\sqrt{1 - \frac{2gb_2}{\omega^2}} \, \alpha_n} f \; e^{i(\alpha_n x - \omega t)}}{\sqrt{1 - \frac{2gb_2}{\omega^2}} \cos\sqrt{\frac{2gb_1}{\omega^2} - 1} \; |\alpha| H - \sqrt{\frac{2gb_1}{\omega^2} - 1} \sin\sqrt{\frac{2gb_1}{\omega^2} - 1} \; |\alpha| H}$$

[A-19]

Introduce dimensionless variables

$$f' = f/H \quad , \quad x' = x/H$$

$$\omega' = \omega/\sqrt{2gb_1}$$

$$N_2' = \sqrt{2gb_2}\Big/\sqrt{2gb_1}$$

$$t' = t\sqrt{2gb_1}$$

Then

$$\tilde{u}_o = +\left(\frac{2\pi M}{H^3}\right)\sum_{n=1}^{\infty} \frac{\alpha_n'^2\, e^{-\alpha_n'\sqrt{1-\frac{N_2'^2}{\omega'^2}}\, f'}\, e^{i(\alpha_n' x' - \omega' t')}}{\sqrt{\frac{\frac{1}{\omega'^2}-1}{1-\frac{N_2'^2}{\omega'^2}}}\,\sin\sqrt{\frac{1}{\omega'^2}-1}\,\alpha_n' - \cos\sqrt{\frac{1}{\omega'^2}-1}\,\alpha_n'}$$

$$[A-20]$$

$$\alpha_n' = \frac{n\pi - \tan^{-1}\sqrt{\frac{\frac{1}{\omega'^2}-1}{1-\frac{N_2'^2}{\omega'^2}}}}{\sqrt{\frac{1}{\omega'^2}-1}}$$

$$[A-21]$$

Write $\tilde{u}_o$ as

$$\tilde{u}_o = \frac{2\pi M}{H^3} (\tilde{u}_1 + \tilde{u}_2 + \dots)$$

Let

$$|\tilde{u}_1| = u_1{}^*$$

$$|\tilde{u}_2| = u_2{}^* \quad \text{etc.}$$

In Figure 6, $u_1{}^*$ and $u_2{}^*$ are plotted as a function of ω' for the special case $b_2 = 0$ and two different depths of submergence.

From the calculation, it is found that the asymptotic surface current is non-zero only when $2gb_2 < \omega^2 < 2gb_1$ (assuming that $2gb_1 > 2gb_2$).

When ω^2 lies within the above range, it is found that the surface current is in the form of a Fourier Series. This is in contrast to calculations for profiles which possess a well defined thermocline. In the latter case, there exists only one Fourier component.

FIGURE I — SCHEMATIC DIAGRAM OF EQUILIBRIUM DENSITY PROFILES

HYDRONAUTICS, INCORPORATED

FIGURE 2 — ASYMPTOTIC WAVE NUMBER FOR DIFFERENT EQUILIBRIUM DENSITY PROFILES

FIGURE 3 — CONFIGURATION OF QUADRUPOLE

FIGURE 4 — EFFECT OF THERMOCLINE THICKNESS

FIGURE 5-EFFECT OF DENSITY GRADIENT IN LOWER LAYER

FIGURE 6 - EFFECT OF DENSITY GRADIENT IN UPPER LAYER

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)	2a. REPORT SECURITY CLASSIFICATION
HYDRONAUTICS, Incorporated, Pindell School Road, Laurel, Maryland	UNCLASSIFIED
	2b. GROUP

3. REPORT TITLE

SURFACE CURRENTS DUE TO A SUBMERGED DISTURBANCE IN A STRATIFIED OCEAN

4. DESCRIPTIVE NOTES (Type of report and inclusive dates)

Technical Report

5. AUTHOR(S) (Last name, first name, initial)

Wong, K. K.

6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
February 1965	34	1
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)	
Nonr-3688(00) NR 220-016	Technical Report 231-6	
b. PROJECT NO.		
c.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.		

10. AVAILABILITY/LIMITATION NOTICES

Qualified requesters may obtain copies of this report from DDC

11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY
	Office of Naval Research Department of the Navy

13. ABSTRACT

Surface currents due to a submerged two-dimensional disturbance of simple harmonic time dependency in a stratified ocean were determined analytically. It was found that the current is a consequence of the formation and propagation of interfacial waves at the thermocline. For large distances from the source of disturbance, the interfacial waves form a regular train of outgoing waves having a definite amplitude and wave number. The surface current also possesses these characteristics. The asymptotic wave number of the surface current is the wave number of free waves at the thermocline.

DD FORM 1473
1 JAN 64

14.		LINK A		LINK B		LINK C	
KEY WORDS		ROLE	WT	ROLE	WT	ROLE	WT
1. Internal wave							
2. Stratified fluids							
3. Water wave							

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through

_____ ."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through

_____ ."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through

_____ ."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.

DD FORM 1 JAN 64 1473 (BACK)

HYDRONAUTICS, Incorporated

DISTRIBUTION LIST
(Contract Nonr-3688(00)

Chief of Naval Research		Commanding Officer and Director	
Department of the Navy		David Taylor Model Basin	
Washington, D. C., 20360		Washington 7, D. C.	1
Attn: Codes 438	2		
416	1	Director	
461	1	U.S. Naval Research Laboratory	
104	1	Washington, D. C. 20360	
406T	1	Attn: Codes 2000	1
427	1	5500	1
402	1	6100	1
446	1	2020	1
466	1	2027	1
		5300	1
Commanding Officer		7300	1
Office of Naval Research		4000	1
Branch Office		5000	1
495 Summer Street		7350	1
Boston 10, Massachusetts	1		
		Chief, Bureau of Ships	
Commanding Officer		Department of the Navy	
Office of Naval Research		Washington, D.C. 20360	
Branch Office		Attn: Codes 305	1
219 S. Dearborn Street		335	1
Chicago, Illinois 60604	1	370	1
		374	1
Commanding Officer		421	1
Office of Naval Research			
Branch Office		Chief, Bureau of Naval Weapons	
207 West 24th Street		Department of the Navy	
New York 11, New York	1	Washington, D.C. 20360	
		Attn: Codes RU-2	1
Commanding Officer		RUDC-43	1
Office of Naval Research		RRRE-4	1
Branch Office			
1030 East Green Street		Chief of Naval Operations	
Pasadena 1, California	1	Department of the Navy	
		Washington, D.C. 20360	
Commanding Officer		Attn: Codes OP-71B	1
Office of Naval Research		OP-07C	1
Branch Office		OP-07T	1
1000 Geary Street		OP-717	1
San Francisco 9, California	1		

Commanding Officer
U.S. Naval Ordnance Laboratory
Corona, California   1

Commander
U.S. Naval Ordnance Test Station
Pasadena Annex
3202 E. Foothill Boulevard
Pasadena 8, California   1

Superintendent
U.S. Naval Postgraduate School
Monterrey, California
Attn: Library   1

Commanding Officer and Director
U.S. Naval Electronic Laboratory
San Diego 52, California   1

Defense Documentation Center
Cameron Station, 5010 Duke St.
Alexandria, Virginia   20

Fluid Mechanics Section
National Bureau of Standards
Washington, D. C. 20360
Attn: Dr. O. B. Schubauer   1

National Research Council
Montreal Road
Ottawa 2, Canada
Attn: Mr. E. S. Turner   1

Institute of Mathematical Sciences
New York University
25 Waverly Place
New York 3, New York
Attn: Prof. J. J. Stoker   1

New York University
Dept. of Oceanography
University Heights
New York 53, New York
Attn: Prof. J.W. Pierson, Jr. 1

The Johns Hopkins University
Baltimore 18, Maryland
Attn: Prof. O. M. Phillips 1

California Institute of Tech.
Pasadena 4, California
Attn: Prof. T.Y. Wu   1

Director
Scripps Institution of
 Oceanography
Applied Oceanography Group
University of California
La Jolla, California   1

Iowa Institute of Hydraulic
 Research
State University of Iowa
Iowa City, Iowa
Attn: Prof. H. Rouse   1

Harvard University
Cambridge 38, Massachusetts
Attn: Prof. G. F. Carrier   1

Massachusetts Institute of
 Technology
Cambridge 39, Massachusetts
Attn: Prof. J. F. Kennedy   1

Stevens Institute of Technology
Davidson Laboratory
Hoboken, New Jersey
Attn: Mr. D. Savitsky   1
       Dr. S. J. Lukasik   1

HYDRONAUTICS, Incorporated

-3-

Director
Woods Hole Oceanographic
  Institute
Woods Hole, Massachusetts
	1	Commander
		U. S. Naval Ordnance Lab.
		White Oak, Maryland
		Attn: Dr. S. J. Raff
		  (DU 5-224)
			1

Dr. B. Zarwyn Airborne Instruments Laboratory Division of Cutler-Hammer Inc. Walt Whitman Road, Melville Long Island, New York	1	Dr. E. Montrell Institute for Defense Analysis 1566 Connecticut Avenue, N. W. Washington, D. C.	1
Mr. Myron J. Block Block Associates, Inc. 385 Putnam Avenue Cambridge 39, Massachusetts	1	Director, Special Projects Office Department of the Navy Washington, D. C. 2035 Attn: Code SP-001	1
Director Hudson Laboratories Dobbs Ferry, New York	1	Dr. I. Katz Applied Physics Laboratory Johns Hopkins University Baltimore 18, Maryland	1
Dr. Savet American Bosch Arma Corporation Arma Division Garden City, New York	1	Dr. Harvey Brooks School of Applied Science Harvard University Cambridge, Massachusetts	1
HYDRONAUTICS, Incorporated Pindell School Road Howard County Laurel, Maryland Attn: Mr. P. Eisenberg, Pres. Mr. M.P. Tulin, V. Pres.	1 1	Arthur D. Little, Inc. 35 Acorn Park Cambridge 40, Massachusetts Attn: Trident Library	1
Dr. L. L. Higgins Space Technology Lab. Inc. Canoga Park Facility 8433 Fallbrook Avenue Canoga Park, California	1	Dr. R. W. Stewart c/o Pacific Naval Laboratory Esquimalt, Vancouver, British Columbia Canada	1
Dr. A. V. Hershey Computation and Exterior Ballistics Laboratory U.S. Naval Weapons Lab. Dahlgren, Virginia	1	Professor M. J. Lighthill Imperial College London, England	1